

CR LAURENCE CO, INC.

ACOUSTICAL PERFORMANCE TEST REPORT

SCOPE OF WORK

ASTM E90 SOUND TRANSMISSION LOSS TESTING ON A D900 TD-42" X 96" DOOR SYSTEM

REPORT NUMBER

H9895.01-303-11 R0

TEST DATE

01/24/18

ISSUE DATE

02/15/18

RECORD RETENTION END DATE

01/24/22

PAGES


14

DOCUMENT CONTROL NUMBER

ATI 00274 (07/24/17)

RT-R-AMER-Test-2756

© 2017 INTERTEK



TEST REPORT FOR CR LAURENCE CO, INC.

Report No.: H9895.01-303-11 r0

Date: 02/15/18

REPORT ISSUED TO

CR LAURENCE CO, INC.

2503 East Vernon Avenue
Los Angeles, California 90058

SECTION 1

SCOPE

Intertek Building & Construction (B&C) was contracted by CR Laurence Co, Inc. to conduct a sound transmission loss test. Results obtained are tested values and were secured by using the designated test method(s). The complete test data is included herein. The client provided the test specimen. All measurements were conducted in the HT test chambers at Intertek B&C located in Lake Forest, California. This report does not constitute certification of this product nor an opinion or endorsement by this laboratory.

SECTION 2

SUMMARY OF TEST RESULTS

SERIES/MODEL	D900 TD-42" x 96"
TYPE	Door System
GLAZING	1" IG (7/16" Laminate Interior, 3/8" Air Space, 3/16" Exterior)
TEST CONDITION	Operable
DATA FILE NO.	H9895.01A
STC	36
OITC	31
AIR INFILTRATION AT 1.57 PSF	0.02 cfm/ft ²
AIR INFILTRATION AT 6.27 PSF	0.06 cfm/ft ²

For INTERTEK B&C:

COMPLETED BY:	Leeland S. Hoover	REVIEWED BY:	Bradley D. Hunt
TITLE:	Technician I	TITLE:	Laboratory Manager
SIGNATURE:		SIGNATURE:	
DATE:	02/15/18	DATE:	02/15/18

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample(s) tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



TEST REPORT FOR CR LAURENCE CO, INC.

Report No.: H9895.01-303-11 r0

Date: 02/15/18

SECTION 3

TEST METHOD(S)

The specimens were evaluated in accordance with the following:

ASTM E90-09 (2016), *Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions and Elements*

ASTM E413-16, *Classification for Rating Sound Insulation*

ASTM E1332-16, *Standard Classification for Rating Outdoor-Indoor Sound Attenuation*

ASTM E2235-04 (2012), *Standard Test Method for Determination of Decay Rates for Use in Sound Insulation Test Methods*

ASTM E283-04(2012), *Standard Test Method for Determining Rate of Air Leakage Through Exterior Windows, Curtain Walls, and Doors Under Specified Pressure Differences Across the Specimen*

SECTION 4

SPECIMEN INSTALLATION

A sound transmission loss test was initially performed on a filler wall.

The specimen plug was removed from the filler wall assembly. A filler wall-reducing element was used to adjust the test opening size to accommodate the test specimen. The reducing element consisted of a double 2x6 wood stud wall construction with three layers of 5/8" drywall on both sides. The stud cavities in the wall were insulated with two layers of R-19 fiberglass insulation. The specimen was placed on an isolation pad in the custom test opening. Duct seal was used to seal the perimeter of the specimen to the test opening on both sides. The interior side of the specimen, when installed, was approximately 1/4" from being flush with the receive room side of the filler wall. A stethoscope was used to check for any abnormal air leaks around the test specimen prior to testing. Operable portions of the test specimen, if any, were cycled at least five times prior to testing.

SECTION 5

EQUIPMENT

The equipment listed below meets the requirements of the test methods stated in Section 3 of this report.

TEST REPORT FOR CR LAURENCE CO, INC.

Report No.: H9895.01-303-11 r0

Date: 02/15/18

INSTRUMENT	MANUFACTURER	MODEL	DESCRIPTION	ASSET #	CAL DATE
Data Acquisition Card	National Instruments	PXIe-4464	Data Acquisition Card	INT00627	10/17 *
Data Acquisition Card	National Instruments	PXIe-4464	Data Acquisition Card	INT00395	10/17 *
Data Acquisition Card	National Instruments	PXIe-4464	Data Acquisition Card	INT00396	10/17 *
Source Room Microphone	PCB Piezotronics	378C20	Microphone and Preamplifier	INT00239	04/17
Source Room Microphone	PCB Piezotronics	378C20	Microphone and Preamplifier	INT00240	04/17
Source Room Microphone	PCB Piezotronics	378C20	Microphone and Preamplifier	INT00241	04/17
Source Room Microphone	PCB Piezotronics	378C20	Microphone and Preamplifier	INT00242	04/17
Source Room Microphone	PCB piezotronics	378C20	Microphone and Preamplifier	INT00243	04/17
Receive Room Microphone	PBC Piezotronics	378C20	Microphone and Preamplifier	INT00244	04/17
Receive Room Microphone	PCB Piezotronics	378C20	Microphone and Preamplifier	INT00245	04/17
Receive Room Microphone	PCB Piezotronics	378C20	Microphone and Preamplifier	INT00246	04/17
Receive Room Microphone	PCB Piezotronics	378C20	Microphone and Preamplifier	INT00247	04/17
Receive Room Microphone	PCB Piezotronics	378C20	Microphone and Preamplifier	INT00228	04/17
Receive Room Environmental Indicator	Comet	T7510	Receive Room	INT00299	10/17
Source Room Environmental Indicator	Comet	T7510	Source Room	INT00300	10/17
Microphone Calibrator	Norsonic	1251	Pistonphone Calibrator	INT00288	06/17

*- Note: The calibration frequency for this equipment is every two years per the manufacturer's recommendation.

TEST CHAMBER

	VOLUME	DESCRIPTION
RECEIVE ROOM	231 m ³	Rotating vane and stationary diffusers Temperature and humidity controlled Isolation pads under the floor
SOURCE ROOM	196 m ³	Stationary diffusers only Temperature and humidity controlled

	MAXIMUM SIZE	DESCRIPTION
TL TEST OPENING	4.27 m wide by 3.05 m high	Vibration break between source and receive rooms

N/A-Not Applicable

SECTION 6

LIST OF OFFICIAL OBSERVERS

NAME	COMPANY
Garrett Osterode	CR Laurence Co, Inc.
Ryan R. Lau	Intertek B&C
Leeland S. Hoover	Intertek B&C

TEST REPORT FOR CR LAURENCE CO, INC.

Report No.: H9895.01-303-11 r0

Date: 02/15/18

SECTION 7

TEST PROCEDURE

Air Infiltration

The air seal between the test specimen and the test wall. The seal is made of foam weatherstripping and is attached to the edge of the test specimen buck. The test specimen buck is placed against the test wall and clamped in place, compressing the weatherstripping and creating a seal. Pressure was applied and the total air infiltration was measured. The specimen exterior was sealed with plastic sheet and duct tape. The extraneous air infiltration was measured. Environmental corrections were applied to the both airflow results. The airflow rate was calculated by subtracting the extraneous airflow from the total airflow and dividing the difference by the specimen area.

Acoustical Tests

The sensitivity of the microphones was checked before measurements were conducted. The transmission loss values were obtained for a single direction of measurement. Two background noise sound pressure level and five sound absorption measurements were conducted at each of five microphone positions. Two sound pressure levels were made simultaneously in the receive and source rooms at each of five microphone positions. The air temperature and relative humidity conditions were monitored and recorded during all measurements. Data for flanking limit tests, repeatability measurements, and reference specimen tests are available upon request.

SECTION 8

ACOUSTICAL TEST CALCULATIONS

Transmission loss (TL) at each 1/3 octave frequency is the average source room sound pressure level minus the average receive room sound pressure level, plus, 10 times the log of the specimen area divided by the sound absorption of the receive room with the sample in place.

STC Rating

To obtain the Sound Transmission Class (STC), read the TL of the contour curve at 500 Hz. The sum of the deficiencies below the contour curve must not exceed 32. The maximum deficiency at any one frequency must not exceed 8.

OITC Rating

The Outdoor-Indoor Transmission Class (OITC) is calculated by subtracting the logarithmic summation of the TL values from the logarithmic summation of the A-weighted transportation noise spectrum stated in ASTM E1332.

TEST REPORT FOR CR LAURENCE CO, INC.

Report No.: H9895.01-303-11 r0

Date: 02/15/18

SECTION 9

SPECIMEN DESCRIPTION

	FRAME	LEAF
SIZE	42" by 96"	40-1/2" by 94-5/8"
THICKNESS	4-1/2"	2-1/4"
CORNERS	Butted	Mitered
FASTENERS	Screws	Keys
SEAL METHOD	Sealant	Sealant
MATERIAL	Aluminum	Aluminum
REINFORCEMENT	N/A	N/A
THERMAL BREAK MATERIAL	Insulbar	Insulbar
DAYLIGHT OPENING SIZE	N/A	33" by 87-1/16"

MEASURED OVERALL INSULATION GLASS UNIT THICKNESS	0.998"
SPACER TYPE	Aluminum box

	EXTERIOR SHEET	GAP	INTERIOR SHEET
MEASURED THICKNESS	0.184"	0.386"	0.182", 0.060", 0.186"
MATERIAL	Heat Strengthened	Air*	Laminated
LAMINATE MATERIAL	N/A	N/A	PVB

GLAZING METHOD	Exterior
GLAZING MATERIAL	Silicone
GLAZING BEAD MATERIAL	Aluminum

	TYPE	QUANTITY	LOCATION
WEATHERSTRIP	1/8" Hollow bulb gasket	1 Row	Perimeter of frame
	1/4" Rubber leaf gasket	1 Row	Perimeter of leaf
HARDWARE	Full mortise butt hinges	4	Hinge stile
	Multi-point Lock and handle	1	Lock stile
DRAINAGE	1-1/4" by 1/2" weep slot with cover	1	Sill
	3/4" by 1/8" weep slot	2	Sill

TOTAL WEIGHT (lbs)	AVERAGE WEIGHT (lbs / ft ²)
366	13.07

* - Stated per Client/Manufacturer, N/A-Not Applicable

TEST REPORT FOR CR LAURENCE CO, INC.

Report No.: H9895.01-303-11 r0

Date: 02/15/18

SECTION 10

TEST RESULTS

ASTM E90 AIRBORNE SOUND TRANSMISSION LOSS



TEST DATE	01/24/18				
DATA FILE NO.	H9895.01A				
CLIENT	CR Laurence Co., Inc.				
DESCRIPTION	Series/Model: D900 TD-42" by 96" Side-Hinged Door with 1" IG (7/16" Laminate Interior, 3/8" Air Space, 3/16" Exterior)				
SPECIMEN AREA	2.60 m ²	RECEIVE TEMP.	18.9 °C	SOURCE TEMP	18.7 °C
TECHNICIAN	Bradlay Hunt	RECEIVE HUMIDITY	40%	SOURCE HUMIDIT	44%

FREQ (Hz)	BACKGROUND SPL (dB)	ABSORPTION (m ²)	SOURCE SPL (dB)	RECEIVE SPL (dB)	SPECIMEN TL (dB)	95% CONFIDENCE LIMIT	NUMBER OF DEFICIENCIES
80	44.1	4.9	104	78	24	1.18	-
100	39.3	4.3	106	78	27	1.30	-
125	45.5	5.0	105	78	25	1.53	0
160	44.7	5.2	104	74	27	1.15	0
200	38.5	6.7	105	77	24	0.61	2
250	29.1	7.1	106	76	25	0.48	4
315	23.5	6.8	106	72	30	0.66	2
400	23.4	5.9	106	69	33	0.48	2
500	18.2	5.4	105	68	34	0.33	2
630	17.0	5.7	106	69	34	0.58	3
800	20.5	5.8	106	68	35	0.42	3
1000	8.3	6.1	107	67	36	0.19	3
1250	5.1	6.3	105	64	37	0.24	3
1600	4.3	7.0	104	62	38	0.14	2
2000	4.0	8.4	101	57	39	0.20	1
2500	3.9	9.6	101	57	38	0.18	2
3150	4.2	11.4	100	54	40	0.23	0
4000	4.8	14.6	98	47	44	0.23	0
5000	5.5	19.5	98	44	45	0.38	-
STC RATING	36 (Sound Transmission Class)						
DEFICIENCIES	29 (Sum of Deficiencies)						
OITC RATING	31 (Outdoor-Indoor Transmission Class)						

- Notes:
- 1) Receive Room levels less than 5 dB above the Background levels are red.
 - 2) Specimen TL levels listed in red indicate the lower limit of the transmission loss.
 - 3) Specimen TL levels listed in green indicate that there has been a filler wall correction applied

TEST REPORT FOR CR LAURENCE CO, INC.

Report No.: H9895.01-303-11 r0

Date: 02/15/18


SECTION 11

RESULTS GRAPH

ASTM E90 AIRBORNE SOUND TRANSMISSION LOSS



TEST DATE	01/24/18				
DATA FILE NO.	H9895.01A				
CLIENT	CR Laurence Co., Inc.				
DESCRIPTION	Series/Model: D900 TD-42" by 96" Side-Hinged Door with 1" IG (7/16" Laminate Interior, 3/8" Air Space, 3/16" Exterior)				
SPECIMEN AREA	2.60 m ²	RECEIVE TEMP.	18.9 °C	SOURCE TEMP	18.7 °C
TECHNICIAN	Bradlay Hunt	RECEIVE HUMIDITY	40%	SOURCE HUMIDIT	44%



TEST REPORT FOR CR LAURENCE CO, INC.

Report No.: H9895.01-303-11 r0

Date: 02/15/18

SECTION 12

PHOTOGRAPHS



Photo No. 1
Source Room View of Test Specimen



Photo No. 2
Receive room



Total Quality. Assured.

TEST REPORT FOR CR LAURENCE CO, INC.


Report No.: H9895.01-303-11 r0

Date: 02/15/18

SECTION 13
DRAWINGS

25800 Commercentre Drive
Lake Forest, California 92630

Telephone: 949-460-9600
Facsimile: 717-764-4129
www.intertek.com/building



① SERIES D900 TERRACE DOOR- OUT-SWING
1 1/2"=1'-0"

ITEM	PT. NO.	PART DESCRIPTION
C1	HT300	BOTTOM RAIL
C2	WN429	GLASS STOP
C3	JH450	FRAME-JAMB
C4	HT450	FRAME-HEAD
C5	HT300	SASH MEMBER
C6	WH751	HINGE ASSEMBLY
C7	WH7633	WEEP HOLE COVERS
W1	WH358	BLADE GASKET
W2	GT416	GLAZING TAPE
W3	WH344	WEDGE GASKET
W4	WH342	BULB GASKET INTERIOR
G1		3/16" CLEAR TEMP-3/8" AIR-3/16" HEAT STRENGTH'ND .060 SOLUTIA PVB-3/16" HEAT STRENGTH'ND
G2	WB410	WEDGE BLOCK
G3	SB222	SETTING BLOCK
G4	SB450	SPACER GASKET
G5	NP267	HOLLOW FORM GASKET
G6	TH701	DEADBOLT STRIKE
G7	TH702	TONGUE STRIKE
G8	TH703	SHOOT BOLT STRIKE
G9	HT451	STANDARD THRESHOLD-OUTSWING
H3	CB291	CORNER BLOCK
H4	----	#10 X 2 1/2" SS WOOD SCREWS
H5	-----	ATHINAL M156/216N-SOLID BRASS W/DEADBOLT
H6	----	#12-24 PH UNDER CUT FLAT HEAD MACHINE SCREWS
S1	EF38C	3/8" CLOSED CELL BACKER ROD
S3	DC795BL	DOW CORNING 795 BLACK-BUILDING SEALANT


TEST REQUIREMENTS	
AIR INFILTRATION:	<0.06 CFM/SQ.FT. @6.24 CFM
STATIC WATER:	15 Psf
DESIGN PRESSURE:	80 Psf
STRUCTURAL OVERLOAD:	120 Psf
TAS-201-94 SMI, LEVEL A WIND ZONE 4	
TAS-202-94 Uniform Static Air Pressure ±80.0psf DP, 15.0psf water	
TAS 203-94 Cyclic Pressure loading ±80.0psf DP	

REVISIONS




Job Name: SERIES D900 TERRACE DOOR
42" X 96" OUTSWING-SMI

Glazing Contractor:	DATE: 8.31.2017
	DRAWN BY: GDO
	CHECKED BY:
	SCALE: AS SHOWN
	JOB #: PTC694395



① OUT-SWING DOOR - HEAD

1-0"=1'-0"



② OUT-SWING DOOR - AT THRESHOLD

1-0"=1'-0"

REVISIONS




C.R. LAURENCE CO.
ARCHITECTURAL PRODUCTS
2100 E. 38TH Street, Los Angeles, CA 90058
www.crlaurence.com

Job Name:
SERIES D900 TERRACE DOOR
42" X 96" OUTSWING-SMI


Glazing Contractor:

DATE: 8.31.2017
DRAWN BY: GDO
CHECKED BY:
SCALE: AS SHOWN
JOB #: PTC694395



③ OUT-SWING DOOR @ JAMB

1-0"=1'-0"



④ OUT-SWING DOOR @ JAMB/LOCK STILE

1-0"=1'-0"

REVISIONS



CRL
 C.R. LAURENCE CO.
 ARCHITECTURAL PRODUCTS

2100 E. 38TH Street, Los Angeles, CA 90058
 www.crlaurence.com

SERIES D900 TERRACE DOOR
 42" X 96" OUTSWING-SMI

Job Name:

Glazing Contractor:

DATE: 8.31.2017
 DRAWN BY: GDO
 CHECKED BY:
 SCALE: AS SHOWN
 JOB #: PTC694395



Total Quality. Assured.

25800 Commercentre Drive
Lake Forest, California 92630

Telephone: 949-460-9600
Facsimile: 717-764-4129
www.intertek.com/building

TEST REPORT FOR CR LAURENCE CO, INC.

Report No.: H9895.01-303-11 r0

Date: 02/15/18

SECTION 14

REVISION LOG

REVISION #	DATE	PAGES	REVISION
0	02/15/18	N/A	Original Report Issue